

# SAFETY DATA SHEET

1. IUCIIIIICalion	1.	Ident	ifica	ation
-------------------	----	-------	-------	-------

Product number	HIL0103055
Product identifier	Gum-Go
Revision date	07-04-2015
Company information	HILLYARD INC 302 North 4th Street St. Joseph, MO 64501 United States
Company phone	816-383-8285
Emergency telephone US	1-800-424-9300
Version #	04
Supersedes date	12-23-2014
Recommended use	Cleaner
Recommended restrictions	None known.

## 2. Hazard(s) identification

Physical hazards	Flammable aerosols	
	Gases under pressure	
Health hazards	Not classified.	
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	Wash hands after handling.
Storage	Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

Category 1 Liquefied gas

## 3. Composition/information on ingredients

Μ	ixtu	res
---	------	-----

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	60 - 80
Propane		74-98-6	20 - 40
Ethyl Alcohol		64-17-5	2.5 - 10
Other components below reportable levels			0.01 - 0.1

#: This substance has workplace exposure limit(s).

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dizziness.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Dry chemical powder. Carbon dioxide (CO2). None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### **Occupational exposure limits**

Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Limit	Values	
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
US. NIOSH: Pocket Guide to	Chemical Hazards	
Components	Туре	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
logical limit values	No biological exposure limits noted	for the ingredient(s).
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
ividual protection measures,	such as personal protective equip	ment
Eye/face protection	Not available.	
Hand protection	Not available.	
Other	Wear suitable protective clothing.	
Respiratory protection	Not available.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
neral hygiene nsiderations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	
Physical and chemical	properties	
pearance	Compressed liquefied gas.	
Physical state	Gas.	
Form	Aerosol. Liquefied gas.	
Color	clear colorless	

Color	clear colorless	
Odor	fruity	
Odor threshold	Not available.	
рН	Not applicable estimated	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	22.1 °F (-5.5 °C) estimated	
Flash point	-156.0 °F (-104.4 °C) Propellant estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	2.6 % estimated	
Flammability limit - upper	12.8 % estimated	

Product name: Gum-Go Product #: HIL0103055 Version #: 04 Revision date: 07-04-2015 Issue date: 12-15-2014

(%)

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 - 70 psig @ 70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	856.4 °F (458 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.57 estimated estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Dizziness.

## Information on toxicological effects

## Acute toxicity

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
	Rat	> 115.9 mg/l, 4 Hours

Components	Specie	s T	est Results	
		5	1.3 mg/l, 6 Hours	
Oral				
LD50	Monkey	/ 6	000 mg/kg	
	Mouse	1	0500 ml/kg	
	Rat	1	187 - 2769 mg/kg	
			800 ml/kg	
Propane (CAS 74-98-6)			5	
Acute				
Inhalation				
LC50	Mouse	1	237 mg/l, 120 Minutes	
		5	2 %, 120 Minutes	
	Rat	1	355 mg/l	
			58 mg/l/4h	
* Estimates for product may	be based on	additional component data not shown.		
Skin corrosion/irritation	Prolonge	d skin contact may cause temporary irritation.		
Serious eye damage/eye rritation	Direct cor	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	on			
Respiratory sensitization		Not available.		
Skin sensitization	This prod	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This prod	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
OSHA Specifically Regulat	ed Substan	ces (29 CFR 1910.1001-1050)		
Not listed.				
Reproductive toxicity	This prod	uct is not expected to cause reproductive or de	evelopmental effects.	
Specific target organ toxicity - single exposure	Not class	Not classified.		
Specific target organ toxicity - repeated exposure	Not class	Not classified.		
Aspiration hazard	Not likely	Not likely, due to the form of the product.		
12 Ecological informatio	n			
12. Ecological informatio		o oguatia lifa		
Ecotoxicity		o aquatic life.		
Components		Species	Test Results	
Ethyl Alcohol (CAS 64-17-5)				
<b>Aquatic</b> Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	r < 100.1 mg/l, 96 nouis	
* Estimates for product may	be based on	additional component data not shown.		
Persistence and degradability		s available on the degradability of this product.		
Bioaccumulative potential	No data a	available.		
Partition coefficient n-octa	nol / water (	log Kow)		
Butane	,	2.89		
Ethyl Alcohol		-0.31		
Propane Mobility in soil	No data a	2.36		
Mobility in soil	No data a	available. adverse environmental effects (e.g. ozone dep	letter sheter best to be the first state of the state of	
Other adverse effects		aguaraa aguraagaatal attaata (a.g. azana dag		

### 13. Disposal considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.		

### 14. Transport information

### DOT

UN1950
Aerosols, flammable, (each not exceeding 1 L capacity)
2.1
-
2.1
Not applicable.
<b>r</b> Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
N82
306
None
None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U

**Packaging Exceptions** Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code DOT

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. LTD QTY Not applicable.



Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

### 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Immediate Hazard - No **Hazard categories** Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

## US state regulations

### **US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

### US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	12-15-2014
Revision date	07-04-2015
Version #	04

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.